
JUST PLYWOOD

TECHNICAL DATA SHEET · HARD-WEARING OVERLAY PLYWOOD

Film Face Plywood (Non-Structural)



A non-structural hardwood plywood with a tough phenolic film face and sealed edges. It's built for surfaces that take a beating, such as truck and trailer floors, boat floors and site work.

Features

- ✓ 165 g/m² phenolic resin film overlay
- ✓ Edges sealed with grey water-resistant coating
- ✓ All-hardwood eucalyptus construction
- ✓ A-bond glue
- ✓ Tight tolerances: ±1 mm length/width, ±0.3 mm thickness
- ✓ Super E0 formaldehyde, FSC chain of custody

Applications

- Truck, trailer and ute tray floors
- Boat floors
- Light-duty formwork and site use
- Workbenches, hoarding and hard-wearing surfaces

Specifications

Construction	All-hardwood eucalyptus
Overlay	165 g/m² phenolic resin film
Edge seal	Grey water-resistant coating
Glue bond	A-bond
Stress grade	Non-structural
Tolerances	Length/width ±1 mm, thickness ±0.3 mm
Formaldehyde emission	Super E0
Chain of custody	FSC

Sizes

Thickness	Size (mm)	Sheets / pack	Pack weight	Approx. weight / sheet
9 mm	2400 × 1200	100	1710 kg	17.1 kg
12 mm	2400 × 1200	75	1710 kg	22.8 kg
17 mm	2400 × 1200	42	1190 kg	28.3 kg

Handling, storage and safety

- Not a structural panel. Use F-graded formply where structural formwork is specified.
- Seal every cut edge.
- Store flat on firm, level ground, dry and under cover.
- Wear gloves, eye protection and a dust mask when cutting.

Typical values from manufacturer's data and test reports. Natural timber products vary. Check that the product suits your project, and follow the engineer's design wherever structural performance is required. Issued November 2026.